



NEW ZEALAND  
WiPath Communications Ltd  
PO Box 761104, Manakau, Auckland 2241  
Unit14/114 Wiri Station Rd, Wiri, Auckland 2104  
P: +64-9-302 1142 E:info@wipath.co.nz

USA  
WiPath Communications LLC  
Apt#1112, 6115 Abbotts Bridge Rd, Johns Creek,  
GA 97 USA  
P: +1-805-907-6707  
E: info@wipath.com

## RCM3000 Relay Control Module for Paging

The RCM3000 is an expansion unit able to be controlled by any of our paging or wireless data products such as the PDT3000, PDR3000. It may also be driven directly from a PC or other serial output device using a simple command protocol. The interface with the controller is RS232.

The RC3000 has 27 individually addressable relays that can be daisy chained with additional RCM3000s using RS232 to create a highly flexible remote control system capable of providing literally hundreds of outputs.



There are a number of ways of addressing the individual relays including a standard message protocol, by Capcode or by a user selectable message text string. ([Download Data Sheet](#))

### Specifications

No. Relay Outputs per board	27
Relay Load Capacity	x25 250VAC 5A/30VDC 7A  x2 250VAC 10A/30VDC 16A
Serial Ports	2 (RJ45 - 3 pins used)
Relay Connector	Screw connectors
Serial Connectors	RJ45
Power	12Vdc
Current	50-100mA plus 16-20mA per activated relay. 800mA max.
Dimensions	188x140x35mm