NEW ZEALAND
WiPath Communications Ltd
Postal: PO Box 8798, Symonds St, Auckland 1150, New Zealand
Street: 3/2 Haultain St, Eden Tce, Auckland, New Zealand
P: +64-9-302 1142 F: +64-9-302 1148 E: info@wipath.co.nz

AUSTRALIA
WiPath Communications Pty Ltd
Postal: PO Box 6947, Silverwater, NSW 2128, Australia
Street: Unit 44, 8 Avenue of Americas, Newington, NSW 2127, Australia
P: +61-2-8004 0535 F: +61-2-9647 1559 E:info@wipath.com.au

Apollo AL/AF-924

Synthesised Pocsag & Crystalled Flex Alphanumeric Pagers
Compact, 3 button operation with one way scrolling
Ideal for users who want a smaller, more discreet pager





Features

- Compact, 3 button operation with one way scrolling
- 4 line zoomable to 2 line display
- 84 character capacity 1 page display (4 line)
- 28,672 character capacity memory
- 6 Capcode capacity (Pocsag) & 16 Capcodes (Flex) which can be Personal or Maildrop with no frame restrictions
- Real Time Clock Calendar
- Time/Date stamp on messages
- Instant message display option
- 16 Personal memory slots, 5 lockable + 10 slots if message full, 5 memo slots & 10 each Maildrop slots
- 5 Daily Alarm sets
- Hand Programmable option
- Message preview of first 1 or 2 lines
- Display Source Address number option
- 8 Melody Alerts, 4 Beep Alerts, Vibe & Sleep modes
- 2, 8, 16, 32 second & continuous Personal alert options
- Nil, beep 1 & 16 second Maildrop alert options
- Delete all function
- Vibe & Beep option
- Duplicate message indicator
- Priority Alert Overide
- Auto Scroll function
- Auto Sleep function
- Unread message display & Reminder alert
- Yellow Backlight with auto on, on receipt of message or manual push button options
- Battery Level indicator and Low Battery alarm
- Option to disable functions: set scroll, pager off, set auto sleep, set alarm, set time, set alert & zoom in/out
- Suitable for Network or Local Area Paging
- 12 Month service warranty

Specifications

Model Codes/Protocols	Pocsag (AL924), Flex (AF924)
Frequencies	132–174 MHz, 443–473 MHz, 929-931 MHz (AL924), 157.950 (AF924)
Baud rate	512 / 1200 / 2400 BPS for POCSAG, 1600 / 3200 / 6400 BPS for FLEX
Sensitivity	512 BPS-5uV/M, 1200 BPS-7uV/M
Spurious Rejection	40db below carrier
Channel Spacing	25 kHz
Selectivity	60db @ 25 kHz
Frequency Deviation	+/- 4.5 kHz
Alert Tone Loudness	82 db @ 10 cm
Weight (with battery)	60g with battery & 80g with battery & holster
Dimensions	Pager: 20 (h) x 62 (l) x 42 mm (w). Display: 45 (l) x 16 mm (w)
Battery	One 1.5 V AAA Alkaline