NEW ZEALAND
WiPath Communications Ltd
Postal: PO Box 8798, Symonds St, Auckland 1150, New Zealand
Street: 3/2 Haultain St, Eden Tce, Auckland, New Zealand
P: +64-9-302 1142 F: +64-9-302 1148 E: info@wipath.co.nz

AUSTRALIA
WiPath Communications Pty Ltd
Postal: PO Box 6947, Silverwater, NSW 2128, Australia
Street: Unit 44, 8 Avenue of Americas, Newington, NSW 2127, Australia
P: +61-2-8004 0535 F: +61-2-9647 1559 E:info@wipath.com.au

Apollo ALA03



Key Specifications/Special Features:

1. Synthesized or Crystal Type
2. Tone / Vibration only pager
3. For guest paging, or nurse paging or church paging
4. PC Programmable
5. Hinged belt clip
6. Charger stand available

AL-A03 Rich Sophistication:

- Tone, vibrate, and flashed alert
- Over the air "off "
- 4 addresses (with four functions per address)
- Programmable Alert type
- One LED (Heartbeat, Alert, Out of range, Low battery)
- One "Push" button to turn pager off
- Ni-MH Rechargeable battery

Specifications:

Model	AL-A03
Frequency	138~174MHz, 408~473MHz
Paging Sensitivity	512bps - 5?V/M, 1200bps - 7?V/M, 2400bps - 9?V/M
Bit Rate	512 / 1200 / 2400bps for POCSAG
Channel Spacing	25Khz
Code Format	POCSAG
Spurious Rejection	40db below carrier
Alert Tone Loudness	85db @ 10 cm
Capcodes	4 Capcodes for POCSAG
Dimension	51 (L) x 74 (W) x 28 (H) mm
Weight	Approximately 76 g